

# MATERIAL SAFETY DATA SHEET

---

## Section 1 - Identification: Company and Product

---

**Company Name and Address:**

Big Wally's Adhesives, Inc.  
75 Southern Avenue  
Brattleboro, VT 05301

**HMIS Rating**

Health:	1
Flammability:	0
Reactivity:	0
PPE:	B

**Contact Name:** Rory Brennan

**Contact Telephone Numbers:**

Non-Emergency – (802) 254-1330  
24 Hour Emergency – CHEMTREC – (800) 424-9300

**Product Name:** Adhesive

**CAS No.:** Mixture

---

## Section 2 – Ingredients

---

Name	CAS#	Percent	TLV
Acrylic Polymer	Non-hazardous	43 – 47	NA
Water	7732-18-5	53 – 57	NA

---

## Section 3 – Physical Data

---

Physical appearance: Thick white liquid	Specific gravity: 1.1
Odor: Acrylic	Vapor density: <1 (water)
pH: 7-9	Freezing point: Same as water
Percent volatile: 55%	Boiling point: Same as water
Water Solubility: Dilutable	

---

## Section 4 – Health Information

---

**Eye Contact:**  
Direct contact may cause slight eye irritation

**Skin Contact:**  
Direct contact may cause slight skin irritation

**Inhalation:**  
Inhalation of vapor or mist may cause irritation of the nose, throat, and lungs, headache, and nausea.

---

## **Section 5 – First Aid Measures**

---

**Eye Contact:**

Flush eyes with plenty of water for 15 minutes. If eye irritation persists, consult a physician.

**Skin Contact:**

Wash affected area with soap and water. If skin irritation persists, consult a physician.

**Inhalation:**

Move to fresh air.

**Ingestion:**

Drink 1 or 2 glasses of water. Consult a physician if necessary. Never give anything by mouth to an unconscious person.

---

## **Section 6 – Personal Protection Equipment**

---

**Eye Protection:**

Safety glasses or goggles

**Hand Protection:**

Appropriate chemically resistant gloves such as those made of neoprene

**Respiratory:**

Use in a well ventilated area

---

## **Section 7 – Fire and Explosion Hazards**

---

Flash Point: Noncombustible

Lower Explosion Limit: Not Applicable

Upper Explosion Limit: Not Applicable

Thermal Decomposition: Thermal decomposition of this material may yield acrylic monomers and oxides of nitrogen.

Extinguishing Media: Use extinguishing media suitable for surrounding fire.

Special Fire Fighting Procedures and Precautions: Material can splatter above 212°F. Dried product can burn. Wear self-contained breathing apparatus and protective suit.

---

## **Section 8 – Accidental Releases**

---

Use personal protection equipment  
Keep away from and upwind of the spill area  
Wet material can create a slippery condition

CAUTION: Keep spills and cleaning runoff from entering municipal sewers and open bodies of water.

---

## **Section 9 – Stability and Reactivity**

---

Hazardous reactions:  
None known. Stable

Materials to avoid:  
None known

Hazardous Polymerization:  
None known

---

## **Section 10 – Disposal**

---

Environmental precautions:  
CAUTION: Keep spills and cleaning runoff from entering municipal sewers and open bodies of water.

Dispose of in accordance with all federal, state, and local regulations.

---

## **Section 11 – Regulatory Information**

---

SARA Title III: Section 311/312:  
This product is not a hazardous chemical under 29CFR1920.1200

SARA Title III: Section 313:  
This product does not contain a chemical which is listed in Section 313 at or above the de minimis reporting concentration.

California (Proposition 65):  
This product contains trace levels of a component or components known to the State of California to cause cancer:

Components:	Ethyl acrylate	140-88-5
	Acrylonitrile	107-13-1
	Formaldehyde	50-00-0